



P TYPE SWING GATE

A combination of high level electronics as well as mechanical security through its range of Gate Security Systems that physically prevents Unauthorized Entrants from entering the premises.

Also can be integrated with an Access Control System from those manufactured by PE that can provide physical Access Control. An optional Integration of a Time and Attendance Recorder from the available range can serve the Dual purpose of Access Control as well as an employee Attendance System.



TECHNICAL SPECIFICATIONS

Supply Voltage	230VAC \pm 10%
Power Consumption	15-40 Watt
Drive Technology	BLDC / Stepper Motor Drive
Communication Protocol	USB or RS485 or RS232
Integration	4 Inputs, 4 PFC outputs & Optional RS485
Access Time Out	0 - 15 sec (Adjustable)
Opening / Closing Speed	2 Sec
Duty Cycle	Intensive use
Cabinet Material	Available in Stainless Steel Grade 304/316 Or Mild Steel
Arm material	Stainless Steel Grade 304
Cabinet Dimension	L 400mm * W 230mm * H 1000mm \pm 5%
Passage Width	950mm
Lane Indicator	Built-in (Green or Red)
Throughput	15-20 persons/minute
M.C.B.F.	10 million cycles
Operating Temperature	-10 to 55° C
Installation	By Anchor Bolts on Plain surface
Included Accessories	Mains Cable, Foundation Bolts etc.
Optional Accessories	Digital IN-OUT Counter, Wireless Remote



PRINT ELECTRONICS EQUIPMENTS

A 2001 Akshar Business Park, Plot no 3 Sector 25, Janta Market Road, Turbhe, Navi Mumbai 400705, India
www.printelectronics.com Contact (Mobile) : +91 9820191652 E-Mail - info@printelectronics.com

GENERAL ARRANGEMENT DRAWING

